

ELECTRIC SCISSOR LIFT

JLG 2630ES 10M HEIGHT

FEATURES

Platform height elevated 7,75 m

Overall width 0,76 m

Platform capacity 230 kg

Roll out deck extension 0,90 m

Fold-down handrails

Lanyard attach points

Proportional hydrostatic drive control with thumb steer

Proportional lift up



GLOBEN

GLOBEN, S.L.

C/Germán Bernácer 95

Elche Parque Empresarial

Apdo. De Correos 5154·03203 **ELCHE** (Alicante)

Telf. **966 299 599** · Móvil 673 823 100

Fax 965 680 523 · info@globen.es

www.globen.es



DIMENSIONS

A. Platform height (elevated)	7.77 m
B. Platform height (lowered)	1.23 m
C. Platform railing height	1.10 m
D. Overall height rails lowered	1.94 m
E. Platform size	0.76 m x 2.30 m
F. Platform extension	0.90 m
G. Overall width	0.76 m
H. Overall length	2.30 m
I. Wheelbase	1.88 m
J. Ground clearance	0.09 m
Platform capacity²	230 kg
Capacity on platform extension	120 kg
Lift/lower time	40/40 sec.
Maximum drive height	7.77 m
Platform weight	2,200 kg
Ground bearing pressure	6.33 kg/cm²
Drive speed lowered	4.4 km/h
Drive speed elevated	0.8 km/h
Gradeability	25%
Turning radius (intern)	0
Turning radius (extern)	2.06 m
Tires	4 x 12.5 Non-marking solid
Brakes	Electric, automatic friction
Drive	24V electric 6 kW
Batteries	4 x 6V 220 A/hr
Charger	(120/240V - 50/60HZ) 20 Amp automatic
Electric motor	3 kW
Hydraulic reservoir	10.6 L

¹Capabilities provided with a maximum of 2 people inside.

